The world of foams for automotive

SEKISUI pilen your reliable partner



Sekisui Pilon is a Sekisui (Japan) company based in Sydney Australia. It specialises in the development, production, sales and marketing of physically and chemically crosslinked, closed-cell Polyolefin Foams.

A team of specialised development and application engineers together with dedicated automotive sales engineers are available for your consultation.

Sekisui Pilon's Sydney plant together with our parent company, Sekisui in Japan, and our sister companies, Sekisui Alveo in Europe, Thai Sekisui in Thailand and Sekisui Voltek in the United States, are your guarantee of quality and reliability world-wide as your polyolefin foam partner.







1-5 Parraweena Rd, Taren Point NSW 2229 Australia PO BOX 2898, Taren Point, NSW 2229 Australia **Web Address:** www.pilon.com.au **Email:** info@pilon.com.au AUSTRALIA Telephone 02 9525 9880 Facsimile: 02 9525 8004 INTERNATIONAL Telephone: (61)-2 -9525 9880 Facsimile: (61)-2-9525 8004





SEKISUI pilon









The increasing trend towards lightweight materials combined with

POLYOLEFIN FOAMS IN

THE AUTOMOTIVE INDUSTRY

noise-reduction properties calls for specialised cost effective materials. Environmentally neutral physically crosslinked polyolefin foam is just such a material. Its unique combination of mechanical, chemical and thermal properties makes it an ideal replacement for traditional foams such as EPDM rubber, polyurethane and PVC.

Sekisui Pilon specialises in the development, production, sales and marketing of physically crosslinked polyolefin foams. The company has the potential to manufacture customised products capable of meeting individual customer requirements.

A major aspect of the company's philosophy is its commitment to total quality including protection for the environment. Our manufacturing process together with our products are environmentally friendly:

- All Sekisui Pilon Foams are manufactured without the use of CFC's or HCFC's.
- Pilon's products enhance the "All Polyolefin Concept" whereby the total composite may be recycled for future alternative use.
- Due to their extremely light weight nature, Sekisui Pilon polyolefin foams are already making a significant contribution to reduced vehicle weight and fuel consumption.

FOAM PROPERTIES

The Sekisui Pilon polyolefin range is specially designed to meet the key requirements for the automotive industry:

- Product flexibility:
 - Wide density range: (25 to 200kg/m^3).
 - Wide thickness
 - range: (between 1.3mm & 50mm).
- Flame retardant characteristics to meet FMVSS 302, and UL 94 HF-1 requirements.
- High property values at low densities.
- Special vacuum forming and press moulding characteristics.
- Thermal Stability.

Sekisui Pilon products also feature the following important properties and characteristics thereby providing many advantages when compared to traditional materials:

• Light weight - up to 84% lighter than PVC foam.

- Wide working temperature (-80°C up to 130°C depending on type).
- Inertness against most chemicals including fuels, oils, brake fluids and cooling liquids.
- Good weathering resistance and ageing behaviour.
- Good cushioning characteristics.
- Fine regular closed cell structure with two process skins.
- Nearly no water absorption, low water vapour transmission.
- Low fogging values.
- Excellent thermoplastic properties, particularly vacuum and press-forming.
- Good thermal and noise insulation properties.
- Odourless and non-toxic.
- Ecologically and chemically neutral.
- Safe disposal by dumping or incineration in the event of recycling not being possible.

AUTOMOTIVE APPLICATIONS

SOFT TRIM

(Door & Side Panels, Seatback, Dashboard, Headliners & ABC Pillars)

- Function: Provides soft feel and smooth contours in conjunction with a variety of cover-stock materials. Soft touch, excellent ageing behaviour compared to Benefits:
 - traditional materials and overall weight and cost savings. Recycling potential.

GASKETS/SEALS

- Function: - Sealing against air, moisture, noise and temperature. - Spacer.
 - Filling of cavities.

Typical examples include: head lamps, tail lamp clusters, heater seals, door trim seals and boot surrounds.

Benefits: Chemical and moisture resistance, less expensive than rubber and most synthetic materials (eg EPDM).

SUN VISORS

Function:	Crash protection with soft feel.
Benefits:	Shock absorption & thermal stability.

WATERSHIELDS

Function:	Sealing against noise and moisture.
Benefits:	No rattling, even at low temperatures, superior vacuum form
	compared to non-crosslinked PP foams and plastic films.

MOTOR UNDERSHIELD

Function:	Sound Deadening.
Benefits:	Thermal stability, chemical inertness (resistant to fuel and

CARPET BACKINGS

Moisture and noise barrier with luxury feel. Function: Heat insulation (reduced condensation), no water absorption Benefits: (no corrosion).

	PILON	Mould Process			Key Application			
	Softlon	VF	LPM	PM	Dashboard	Doorpanel	Headliner	Watershiel
PP	SPV	++			Х	Х		
	SPVA	+++			Х	Х		
	SPSMK	+	++	+++	Х	Х		
	SPLPM	+	+++	++	Х	Х		
PE	SVF	++				Х	Х	Х
	S	+					Х	Х

PM= Press Moulding, VF=Vacuum Forming, LPM = Low Pressure Moulding

- - Key Product line in automotive application



nabilitv

id oils).













