



# **SAFETY DATA SHEET**

# Silent<sup>TM</sup> Shield Flooring Underlay

### Introduction

This Safety Data Sheet contains the following information and advice.

#### Contents

- 1. Identification of:
  - 1.1 Product
  - 1.2 Company
- 2. Product Description
- 3. Hazards Identification
- 4. First Aid Measures
- 5. Fire Fighting Measures
- 6. Accidental Release Measures
- 7. Handling and Storage
- 8. Exposure Controls / Personal Protection
- 9. Physical and Chemical Properties
- 10. Stability and Reactivity
- 11. Toxicological Information
- 12. Ecological Information
- 13. Recycling & Disposal Considerations
- 14. Transport Information
- 15. Regulatory Information
- 16. Other Information





### 1. Identification of:

1.1 **Product** Silent<sup>TM</sup> Shield Standard

Silent<sup>TM</sup> Shield Professional Silent<sup>TM</sup> Shield Premium Silent<sup>TM</sup> Shield Screed SD Silent<sup>TM</sup> Shield Screed HD Silent<sup>TM</sup> Shield Screed UHD

**1.2** Company Thai Sekisui Foam Co., Ltd.

700/379 Moo 6,

Tumbol Donhua-loh, Amphur Muang

Chonburi 20000, THAILAND

Tel: +66 3821 3219 ~ 26 Fax: +66 3821 3281

# 2. Product Description

Silent<sup>TM</sup> Shield is based on physically crosslinked polyolefin foam produced in a continuous web process. Silent<sup>TM</sup> Shield is based on PE homo and copolymers and foamed with an organic foaming agent by chemical decomposition. The two following gases are mainly produced:

- Nitrogen (N<sub>2</sub>)
- Carbon dioxide (CO<sub>2</sub>)

Both are known as non-depleting substances to the ozone layer.

Some products may be faced with a polyolefin based film.

### 3. Hazards Identification

Health Effect: Not classified as hazardous according to EU Regulation

1272/2008/EC (CLP/GHS).

Polyolefin foam will burn when provided with an adequate amount of heat and oxygen, therefore do not expose the material to any flame or other source of ignition or heat. Subject to reasonable care and cleanliness there are no obvious problems associated with the handling of polyolefin foams.

#### 4. First Aid Measures

After contact with skin: No special measures with usage at normal temperatures.

After contact with eyes: Flush thoroughly with flowing water.

After inhalation: No special measures with usage at normal temperatures.

After swallowing: If ingested, induce vomiting by drinking a large volume of water

or salt water. Seek medical attention.





In case of fire:

If smoke gases are inhaled, which contain mainly carbon dioxide (CO<sub>2</sub>) and carbon monoxide (CO), fresh air and possible artificial respiration (seek medical attention immediately) are the recommended measures.

If body skin is burned through contact with molten material, cool burned parts with water but do not remove from the skin. If skin burn degree 2 or 3 is reached, seek medical attention immediately.

# 5. Fire Fighting Measures

Fire extinguishing mediums are:

- Dry chemical
- Water spray
- Extinguishing foam
- CO<sub>2</sub> extinguisher

Use respirator/oxygen masks in enclosed areas. Avoid dense smoke and do not inhale the smoke gases from combustion.

Use safety glasses and protect skin/body with protective clothing.

### 6. Accidental Release Measures

Not applicable.

# 7. Handling and Storage

#### Handling:

Practice reasonable care as a normal safety precaution. The working environment should be kept clean and free of dust.

Fabrication areas should be well ventilated to carry away fumes, vapours and dust, especially in processes, e.g. lamination (heat and coating), welding, vacuum forming, hot press moulding; operators should be assured of a supply of fresh air.

#### Storage:

Practice reasonable care and cleanliness; provide adequate distance between stacks as a safety precaution. Store inside with adequate ventilation and keep dry, away from direct sunlight. Keep in original packing until required. Do not expose to any source of flame, ignition or heat.

# 8. Exposure Controls/Personal Protection

Breathing protection:

No special requirements.

Hand protection:

Use safety gloves when cutting product with a knife.

Eye protection:





No special requirements.

**Body protection:** 

No special requirements.

# 9. Physical and Chemical Properties

### Appearance:

Semi rigid closed cell, physically crosslinked polyolefin foam. Some products may be faced with a polyolefin based film.

Odour: Odourless

Softening range:  $\geq 100 - 130^{\circ}C$ 

Autoflammability: ≥300°C

Thermal decomposition:  $>160-180^{\circ}C$ 

Explosive properties:

Solubility in water:

None
Insoluble

organic solvents: Insoluble, partly soluble, swelling;

depending on solvent type

Electrical surface resistance:  $\geq 10^{18} \Omega$ .cm

# 10. Stability and Reactivity

Avoid:

Any temperature (over period >10 minutes) >160 - 180°C

Any contact with strong oxidising chemicals

# 11. Toxicological Information

Toxicologically harmless:

Physically crosslinked polyolefin foams are among the most inert polymer foams and constitute no hazard in terms of normal handling and skin contact.

# 12. Ecological Information

Environmentally harmless:

- Insoluble in water.
- Insoluble in most solvents.
- Free of heavy metals and plasticisers.
- Degradable only by prolonged UV exposure.

#### Ozone layer depleting substances:

Silent<sup>TM</sup> Shield does not contain and is not produced with any of the substances mentioned in the "Montreal Protocol" of ozone depleting substances and in the corresponding EC Regulation 2009/1005:

- Chlorofluorocarbons (CFCs)
- Hydrochlorofluorocarbons (HCFCs)
- Carbon Tetrachloride
- 1,1,1-Trichloroethane
- Methyl Bromide
- Hydrobromofluorocarbons (HBFCs)





# 13. Recycling & Disposal Considerations

#### Re-use:

Remnant material may be reused directly, e.g:

Cushion packaging material

#### Recycling:

Ask our Sales Engineers about product specific recycling possibilities.

#### Disposal:

When disposing of any waste, observe all applicable national and local regulations. Silent<sup>TM</sup> Shield may be disposed of by:

- Landfill
  - Physically crosslinked polyolefin foam is inert and does not degrade, it forms a permanent soil base and releases no gases or chemicals known to pollute water resources.
- Incineration
   Incinerate using properly controlled municipal or industrial incineration systems. Plastic materials, such as physically crosslinked polyolefin foam, have high heat values and should only be incinerated in units designed to handle high combustion heat.

### 14. Transport information

No restrictions and non-hazardous material in relation to transportation regulations.

# 15. Regulatory information

No regulations apply in relation to classification, packaging and identification, also applicable to health and environmental care.

### 16. Other information

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe the product from the point of view of safety requirements, and is not intended to guarantee any particular properties.



This information on Sekisui Foam International products is presented to the best of our knowledge. All product data is based on average values and is for guidance only. As these products are subject to constant research and development, we reserve the right to update the contents without notice.



Recommendations as to methods of post fabrication, application and use of Sekisui Foam International products are based on our experience and knowledge of the characteristics of our products and are given in good faith. As producer of the material we have no control over the application of Sekisui Foam International products and no legal responsibility is accepted for such recommendations. In particular, no responsibility is accepted by us for any system in which Sekisui Foam International products are utilised or for any application.

**Softlon** and **Thermobreak** – Registered trademarks of Sekisui Chemical Co. Ltd or its subsidiaries.

© Sekisui Pilon Pty Ltd. Date of Publication: 17 June 2020.